

## SOFAR 15K~20KTLX-G3

15 / 20kW

SOFAR

THREE-PHASE DUAL-MPPTS

---



### Product advantages

- Maximum efficiency 98.6%
- Low start-up voltage, wide MPPT voltage
- Maximum DC input voltage 1100 V
- Smart string level monitoring
- Type II SPD for both DC and AC side
- Remote firmware upgrade
- 110% long-time overload ability



Datasheet	SOFAR 15KTLX-G3	SOFAR 17KTLX-G3	SOFAR 20KTLX-G3	SOFAR 22KTLX-G3	SOFAR 24KTLX-G3
<b>Input (DC)</b>					
Recommended max. PV input power (Wp)	22500	25500	30000	33000	36000
Max. DC power for single MPPT (W)	15000		16500		18000
Number of MPP trackers	2				
Number of DC inputs	2 / 2				
Max. input voltage (V)	1100				
Start-up voltage (V)	160				
Rated input voltage (V)	650				
MPPT operating voltage range (V)	140-1000				
Full power MPPT voltage range (V)	420-850	450-850	480-850	510-850	540-850
Max. input MPPT current (A)	26 / 26				
Max. input short circuit current per MPPT (A)	36 / 36				
<b>Output (AC)</b>					
Rated power (W)	15000	17000	20000	22000	24000
Max. AC power (VA)	16500	18700	22000	24200	26400
Max. output current (A)	23,9	27,1	31,9	35,1	38,3
Rated grid voltage	3 / N / PE, 230 / 400 Vac				
Grid voltage range	310 - 480 Vac (according to local standard)				
Rated grid frequency	50 Hz / 60 Hz				
Grid frequency range	45 Hz-55 Hz / 55 Hz-65 Hz (according to local standard)				
THDi	< 3%				
Power factor	1 default (adjustable +/-0.8)				
<b>Efficiency</b>					
Max. efficiency	98.6%				
European efficiency	98.2%				
<b>Protection</b>					
DC reverse polarity protection	Yes				
Anti-islanding protection	Yes				
Leakage current protection	Yes				
Ground fault monitoring	Yes				
PV-array string fault monitoring	Yes				
Anti reverse power function	Yes				
DC switch	Yes				
Input / output SPD	PV: type II standard, AC: type II standard				
<b>Communication</b>					
Standard Communication mode	RS485/Bluetooth, Optional: WiFi/Ethernet				
<b>General Data</b>					
Topology	Transformerless				
Ambient temperature range	-30°C ~ +60°C				
Self-consumption at night (W)	< 1				
Allowable relative humidity range	0-100%				
Cooling	Fan				
Max. operating altitude	4000 m				
Dimension (mm)	520*430*189				
Weight (kg)	20	22		23	
Display	LCD, App via Bluetooth				
Degree of protection	IP65				
<b>Standard</b>					
EMC	EN 61000-6-1, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12				
Safety standards	IEC 62109-1 / 2, IEC62116, IEC 61727, IEC61683, IEC 60068 (1, 2, 14, 30)				
Grid standards	VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, CEI 0-21 / CEI 0-16, UNE 206 007-1, EN 50549, G98 / G99, EN 50530,				

\* All specifications are subject to change without notice.